



บริษัท ฟลูเทค จำกัด
Flu-tech co.,ltd
Authorized Distributor

PRODUCT INFORMATION

SHUTTLE & QUICK EXHAUST VALVES

18 & 19 SERIES



ROSS CONTROLS

The diagram shows a closed-loop hydraulic circuit. It consists of two pumps (represented by circles with an inscribed triangle) and two actuators (represented by circles with a horizontal line through the center). The pumps are connected in series to the actuators. The flow path is indicated by arrows: from the first pump, through the first actuator, then through the second pump, and finally through the second actuator, returning to the first pump. The components are labeled with numbers: 1 for the first pump, 2 for the second pump, and 3 for the first actuator.

[illegible]

Construction Design	Poppet	Flow Media	Filtered air
Mounting Type	In-line	Operating Pressure	5 to 150 psig (0.3 to 10 bar)
Temperature	Ambient/Media: -40° to 175°F (-40° to 80°C) <i>For temperatures below 40°F (4°C) air must be free of water vapor to prevent formation of ice.</i> <i>For temperatures below -40°F (-40°C), consult ROSS.</i>	Construction Material	Valve Body: Cast Aluminum

 WWW.FLUTECH.CO.TH
 SALES@FLUTECH.CO.TH
 + 66 (0) 2384-6060
 + 66 (0) 2384-5701



บริษัท ฟลูเทค จำกัด
FLU-TECH CO.,LTD

845/3-4 หมู่ 3 ถ.เทพารักษ์ ต.เทพารักษ์ อ.เมือง จ.สมุทรปราการ 10270

845/3-4 Thepharak RD., T.Thepharak, A.Muang, Samutprakarn 10270 THAILAND
Tel. 0 2384 6060, Fax 0 2384 5701, Email : pneumatic@flutech.co.th, www.flutech.co.th