

























### 9.4. Ordering chart

#### Transmitter Type SE10 for sensor-fitting Type S010

Output	Electrical connection	Article no.
Reed contact, NO	Cable plug EN 175301-803	438087
Reed contact, NC	Cable plug EN 175301-803	438088

#### Sensor-fitting Type S010

Port connection	Standard	Article no. Range 1					Article no. Range 2		
		DN 15	DN 20	DN 25	DN 32	DN 40	DN 32	DN 40	DN 50
		<b>Brass, seal in FKM - Temperature max. 55 °C, PN 16</b>							
Internal thread	G	438163	438164	438165	438166	438167	438169	438170	438171
	NPT	438172	438173	438174	438175	438176	438178	438179	438180
	Rc	438181	438182	438183	438184	438185	438187	438188	438189
<b>Stainless steel, seal in FKM - Temperature max. 55 °C, PN 16</b>									
Internal thread	G	438199	438200	438201	438202	438203	438205	438206	438207
	NPT	438208	438209	438210	438211	438212	438214	438215	438216
	Rc	438217	438218	438219	438220	438221	438223	438224	438225
External thread	G	438226	438227	1.)	1.)	1.)	1.)	1.)	1.)
Weld ends	EN ISO 1127/ ISO 4200/ DIN 11866 series B	438235	1.)	438237	1.)	1.)	1.)	1.)	438243
<b>PVC, seal in FKM - Temperature max. 50 °C, PN 10</b>									
True union	DIN 8063	438091	438092	438093	438094	438095	438097	438098	438099
	ASTM D 1785/76	438109	438110	438111	438112	438113	438115	438116	438117
	JIS 10K	438118	438119	438120	1.)	438122	1.)	438125	438126
Spigot	DIN 8063	438100	1.)	438102	438103	438104	1.)	1.)	1.)
<b>PP, seal in FKM - Temperature max. 55 °C, PN 10</b>									
True union	DIN 16962	438127	438128	438129	1.)	438131	438133	1.)	1.)
Spigot	DIN 16962	1.)	1.)	438138	1.)	438140	1.)	1.)	438144

1.) On request

#### Further versions on request

	<b>Process connection</b> <ul style="list-style-type: none"> <li>Weld ends SMS 3008, BS 4825-1/ASME BPE/ DIN 11866 series C or DIN 11850 series 2/ DIN 11866 series A/DIN EN 10357 series A</li> <li>Clamp DIN 32676 series B, SMS 3017, BS 4825-3/ ASME BPE or DIN 32676 series A</li> <li>Flange EN 1092-1/B1/PN 16, ANSI B16-5 or JIS 10K</li> <li>True union ISO 10931</li> <li>Spigot ISO 10931</li> </ul>		<b>Material</b> PVDF - Temperature max. 55 °C, PN 10
--	---	--	---

## 9.5. Ordering chart accessories

## Seals for sensor-fitting body

Specification	Article no.					
	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50
In FKM for sensor-fitting in metal	426340 ☒	426340 ☒	426340 ☒	426340 ☒	426340 ☒	426340 ☒
In EPDM for sensor-fitting in metal	426341 ☒	426341 ☒	426341 ☒	426341 ☒	426341 ☒	426341 ☒
In FKM for sensor-fitting in plastic	431555 ☒	431556 ☒	431557 ☒	431558 ☒	431559 ☒	431560 ☒
In EPDM for sensor-fitting in plastic	431561 ☒	431562 ☒	431563 ☒	431564 ☒	431565 ☒	431566 ☒

## Sensor holder and cable plug

Description	Article no.
Brass with short blade "range 1", seal in FKM, screws for DN 15...DN 40	561761 ☒
Brass with long blade "range 2", seal in FKM, screws for DN 32...DN 50	560906 ☒
Female cable plug EN 175301-803 with cable gland - see <b>Type 2518</b> ▶	572264 ☒
Female cable plug EN 175301-803 with NPT ½" reduction without cable gland - see <b>Type 2509</b> ▶	162673 ☒

## Further versions on request

Material
Stainless steel sensor holder