

TUBE-AWAY KITS



Tube-Away kits for all general purpose and coalescent filters are available to carry liquid drainage to a remote disposal point. Order by the part numbers below.

- With 3-ft (1-meter) tubing.....K802-21-3
- With 6-ft (2-meter) tubing.....K802-21-6
- With 12-ft (4-meter) tubing.....K802-21-12

QUICK-FILL CAP FOR LUBRICATORS

Quick-fill caps (Q-caps) are check-valve fittings for filling lubricators. They can be ordered as a lubricator option, and are also available by the following part numbers.



Usage	Part Number	Threads
MINIATURE		
SENTRY	A203-8BH	3/8-24
GUARDSMAN		
SERIES 380	KA117-109	1/2-13
VANGUARD	A204-8BH	1/2-13

QUICK-FILL HOSE COUPLER



A10001

1/8-NPTF

Female Connector

The quick-fill hose coupler is used on the end of a oil fill hose assembly to attach to a Quick-Fill Cap. This allows easier oil refills on a lubricator. See each product breakdown chart for available order options.

Quick-Fill caps can be ordered either on the product or purchased separately (Shown above).

PRESSURE GAUGES



Gauges are made with "shatter-proof" plastic faces for use in rugged environments. Large numerals show psig in black and bar in red. Heavy duty construction of bourdon and indicator dial. Accuracy is within 2 to 3 percent.

All regulators and assemblies with regulators include a gauge. **SENTRY** and **MINIATURE** models have a 1/8 NPT connection, and 1-1/2 inch diameter gauge face. All other models have a 1/4 NPT pipe connection, and the gauge face is 2 inches (51 mm) in diameter. Gauges are also available by the following part numbers.

Pressure Range psig (bar)	Dial Diameter inch (mm)	Pipe † Connection NPT	Part Number
0-30 (0-2.1)	2 (51)	1/4	30BDD
0-60 (0-4.1)	2 (51)	1/4	60BDD
0-200 (0-13.8)	2 (51)	1/4	200-BDD
0-600 (0-41.4)	2 (51)	1/4	600-BDD
0-30 (0-2.1)	1.5 (38)	1/8	30MDD
0-60 (0-4.1)	1.5 (38)	1/8	60MDD
0-160 (0-11)	1.5 (38)	1/8	70MDD

† Back mounting connection.

PRESSURE GAUGES

For HPR100 and HPR180 Models



Following kits reflect reducer bushing with pressure gauges to fit all required gauge ports for both series. See **HPR100** and **HPR180** pages for details on port sizes required.

PORT SIZE	RANGE	GAUGE KIT
1/4-NPTF	0-200 PSI	A200-BDD-2
1/4-BSPT	0-200 PSI	A200-BDD-2W
3/8-NPTF	0-200 PSI	A200-BDD-3
3/8-BSPT	0-200 PSI	A200-BDD-3W
1/2-NPTF	0-200 PSI	A200-BDD-4
1/2-BSPT	0-200 PSI	A200-BDD-4W
1/4-NPTF	0-600 PSI	A600-BDD-2
1/4-BSPT	0-600 PSI	A600-BDD-2W
3/8-NPTF	0-600 PSI	A600-BDD-3
3/8-BSPT	0-600 PSI	A600-BDD-3W
1/2-NPTF	0-600 PSI	A600-BDD-4
1/2-BSPT	0-600 PSI	A600-BDD-4W



บริษัท ฟลูเทค จำกัด
FLU-TECH CO.,LTD

845/3-4 หมู่ 3 ถ.เทพารักษ์ ต.เทพารักษ์ อ.เมือง จ.สมุทรปราการ 10270

845/3-4 Thepharak RD., T.Thepharak, A.Muang, Samutprakarn 10270 THAILAND

Tel. 0 2384 6060, Fax 0 2384 5701, Email : sales@flutech.co.th, www.flutech.co.th