

## HED402

### Auto Drain



#### HED402 Auto Drain

#### ◎ Purpose

This product often applies to the low places of auto-remove piping, frozen type air drying machine, oil separator, air storage tank and the bottom of various air filters. It can be installed in the places which are not convenient for manual discharge of sewage, such as high, low, narrow places. Especially, it can be installed in the places with large consumption of air or frequent drain times, to prevent the compressed air to be re-polluted by condensed water resulting from the neglect of manual drain.


#### ◎ Features

Auto drain/ Zero pressure drain/ The water cup with metal bowl guard.

#### ◎ Attention

The drainer should be installed vertically and the port should face down, when using.

#### ◎ Main Dimension



Model	HED402-02	HED402-03	HED402-04
Working medium	Compressed air		
Working pressure (MPa)	0.15~1.0		
Guaranteed pressure resistance (MPa)	1.5		
Working temperature (°C)	5~60		
Port size	G1/4	G3/8	G1/2
Drain port size	G1/8		
Drain status	Normal open		

## FLU-TECH CO. LTD.

**Email:** sales@flutech.co.th **Website:** <https://flutech.co.th>

**Tel:** 02-384-6060, 086-369-5871-3 **Fax:** 02-384-5701 **LINE OA:** @flutech.co.th

**Address (HQ):** 845/3-4, Moo 3, Theparak Rd., T. Theparak, A. Mueang Samut Prakan, Samut Prakan, 10270, Thailand

